

S.L. 000-5  
7-15-76

# **FIAT SERVICE LETTER**

**SUBJECT: WHEEL ALIGNMENT**

**VEHICLES: ALL MODELS**

**GENERAL INFORMATION:**

The enclosed chart contains the revised wheel alignment specifications for all 1976 models.

Proper wheel alignment adjustments will insure ideal handling and operating qualities under normal driving conditions.

The attached specifications can also apply to 1975 models.

**NOTE:** This service letter is to be in addition to S.L. 000-5.  
Keep both letters under index number 000-5.

READ, INITIAL AND PASS ON

Service Manager	Parts Manager	Service Writer	Technician			

# WHEEL ALIGNMENT 1976 MODELS

FRONT				
MODEL	TOE-IN		CAMBER	CASTER
	in.	mm.		
128 Sedan, S.W.	-.118 to +.039	-3 to +1	+1°10' to +2°10'	+1°10' to +2°10'
128 3P	-.059 to +.100	-1.5 to +2.5	+0°50' to +1°50'	+1°10' to +2°10'
X 1/9	+.079 to +.236	+2 to +6	0° to -1°	+6°30' to +7°30'
131 2-4 Door & S.W.	+.157 to +.314	+4 to +8	+0°25' to +1°25'	+3°15' to +4°15'
124 Sport Spyder	+.157 to +.314	+4 to +8	-0°20' to +0°40'	+2°40' to +3°40'

## REAR

128 Sedan	+.059 to +.217	+1.5 to +5.5	-0°40' to +0°20'	-----
128 S.W.	+.059 to +.217	+1.5 to +5.5	+0°10' to +1°10'	-----
128 3P	+.079 to +.236	+2 to +6	-0°40' to -1°40'	-----
X 1/9	+.157 to +.314	+4 to +8	-1°10' to -2°10'	-----

NOTE: The above data applies to an unladen vehicle.